

TECHNICAL SHEET MANIPAV LASER M-2500

| | |
|--------------------------------------|--|
| WEIGHT | 850 KG |
| ENGINE | AIR COOLED, 20 HP-KHOLER |
| BATTERY | 12V /60 AH |
| PETROL TANK | 12L |
| CONTROL | ELECTRIC/HYDRAULIC |
| DRIVE | 3 HYDRAULICS ENGINES WITH GEARBOXES |
| VIBRATION | VIBRATING RULE 300 cm ELECTRIC VIBRATOR 3000 rpm |
| OIL TANK | 60 L IN FRAME |
| HYDRAULIC CYLINDER LASER | 48 cm HIGH |
| WHEELS | 6 UNITS. WITH RUBBER (ANTI-PUNCTURE) |
| DISTANCE FROM THE FLOOR | 25 cm |
| LASER | SPECTRA 1 CONTROL BOX CB-30 2 RECEIVERS LR-30 KIT CONECTION |
| TRANSPORT DIMENSIONS | |
| TOTAL LENGTH | 300 cm |
| TOTAL WIIDTH | 200 cm |
| TOTAL HEIGHT | 160 cm |
| WORK DIMENSIONS | |
| TOTAL LENGTH | 310 cm |
| TOTAL WIDTH (Vibrating rule) | 300 cm |
| TOTAL HEIGHT | 200 cm |
| LASER SUPPORT | 50 cm |
| PRODUCTION | 350 m2/h |

