

## FICHE TECHNIQUE MANIPAV LASER M-2500

<b>POIDS</b>	850 KG
<b>MOTEUR</b>	AIR COOLED, 20 HP-KHOLER
<b>BATTERIE</b>	12V /60 AH
<b>RÉSERVOIR DE GAS-OIL</b>	12L
<b>CONTRÔLE</b>	ELECTRIC/HYDRAULIC
<b>TRACTION</b>	3 HYDRAULICS ENGINES WITH GEARBOXES
<b>VIBRATION</b>	VIBRATING RULE 300 cm ELECTRIC VIBRATOR 3000 rpm
<b>DIPÒSIT OLI</b>	60 L IN FRAME
<b>CYLINDRE HYDRAULIQUE LASER</b>	48 cm HIGH
<b>PNEUS</b>	6 UNITS. WITH RUBBER (ANTI-PUNCTURE)
<b>SÉPARATION DU SOL</b>	25 cm
<b>NETTOYAGE</b>	SPECTRA 1 CONTROL BOX CB-30 2 RECEIVERS LR-30 KIT CONECTION
<b>DIMENSIONS DE TRANSPORT</b>	
<b>LONGUEUR TOTALE</b>	300 cm
<b>LARGEUR TOTALE</b>	200 cm
<b>HAUTEUR TOTALE</b>	160 cm
<b>DIMENSIONS DE TRAVAIL</b>	
<b>LONGUEUR TOTALE</b>	310 cm
<b>LARGEUR TOTALE ( Règle vibrante)</b>	300 cm
<b>HAUTEUR TOTALE</b>	200 cm
<b>SUPPORT LASER</b>	50 cm
<b>PRODUCTION</b>	350 m <sup>2</sup> /h

